




**Model Number**

**NBB1,5-5GM25-E2-V3**

**Features**

- Basic series
- 1.5 mm embeddable

**Connection**



**Pinout**




Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)

**Accessories**

- V3-WM**  
Female connector, M8, 3-pin, field attachable
- V3-GM**  
Female connector, M8, 3-pin, field attachable
- V3-GM-2M-PUR**  
Cable socket, M8, 3-pin, PUR cable
- V3-WM-2M-PUR**  
Cable socket, M8, 3-pin, PUR cable
- BF 5**  
Mounting flange, 5 mm

**Dimensions**



**Technical Data**

**General specifications**

Switching element function		PNP	NO
Rated operating distance	$s_n$	1.5 mm	
Installation		embeddable	
Output polarity		DC	
Assured operating distance	$s_a$	0 ... 1.215 mm	
Reduction factor $r_{AI}$		0.4	
Reduction factor $r_{Cu}$		0.4	
Reduction factor $r_{303}$		0.75	

**Nominal ratings**

Operating voltage	$U_B$	10 ... 30 V
Switching frequency	$f$	0 ... 3000 Hz
Reverse polarity protected		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	$U_d$	$\leq 2$ V
Operating current	$I_L$	0 ... 200 mA
Off-state current	$I_r$	0 ... 0.1 mA typ. 0.1 $\mu$ A at 25 °C
No-load supply current	$I_0$	$\leq 10$ mA
Indication of the switching state		LED, yellow

**Ambient conditions**

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

**Mechanical specifications**

Connection type	Device connector M8 x 1, 3-pin
Sensing face	PBT
Protection degree	IP67

**Compliance with standards and directives**

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

**Approvals and certificates**

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Products with a maximum operating voltage of $\leq 36$ V do not bear a CCC marking because they do not require approval.

Release date: 2011-07-06 15:24 Date of issue: 2011-07-06 182308\_eng.xml